

- Operating method of membrane separation apparatus for purifying waste water, involves supplying biological treatment liquid **mixed** with gas to membrane separation unit, **clean** film elements of membrane separation unit.

L20 ANSWER 75 OF 121 WPINDEX COPYRIGHT 2002 DERWENT INFORMATION LTD
AN 2001-568380 [64] WPINDEX
DNC C2001-168995
DC D15 J01
PA (DAIEL) DAICEL CHEM IND LTD
CYC 1
PI JP 2001205055 A 20010731 (200164)* 6p
ADT JP 2001205055 A JP 2000-22196 20000131
PRAI JP 2000-22196 20000131
AN 2001-568380 [64] WPINDEX
AB JP2001205055 A UPAB: 20011105
NOVELTY - Initially the filtering operation is stopped, and a circulating pump (3) is made to mix gas with biological treatment liquid of a bioreaction tank (1) and is supplied to **membrane** separation unit, to **clean** film elements (6) of membrane separation unit. The gas bubbles are removed from liquid and the liquid is returned to bioreaction tank. The cleaning operation of film elements is performed intermittently.
DETAILED DESCRIPTION - An INDEPENDENT CLAIM is also included for membrane separation apparatus.
USE - For purifying domestic, industrial waste water, human waste etc.
ADVANTAGE - The adherence of sludge to film element is reduced by contacting gas bubbles with film elements, hence filtration efficiency of film element is enhanced. Excess aeration is prevented, since gas bubbles are removed from liquid before being returned to bioreaction tank.
DESCRIPTION OF DRAWING(S) - The figure shows the outline diagram of membrane separation apparatus. (Drawing includes non-English language text).
Bioreaction tank 1
Circulating pump 3
Film elements 6
Dwg.1/1